

Maxwell Service

Install

```
# yum install -y hubzero-mw-service
```

Configure

```
# mkvztemplate amd64 squeeze shira
```

```
# hzcms configure mw-service --enable
```

Test

```
# maxwell_service startvnc 1 800x600 24
```

Enter an 8 character password when prompted (e.g., "testtest")

This should result in a newly create OpenVZ session with an instance of a VNC server running inside of it. The output of the above command should look something like:

```
Reading passphrase:
testtest
===== begin /etc/vz/conf/hub-
session-5.0-amd64.umount =====

Removing /var/lib/vz/root/1 :root etc var tmp dev/shm dev
===== end /etc/vz/conf/hub-
session-5.0-amd64.umount =====
stunnel already running
Starting VE ...
===== begin /etc/vz/conf/1.mount =====
=====
Removing and repopulating: root etc var tmp dev
Mounting: /var/lib/vz/template/debian-5.0-amd64-maxwell home apps
```

MAXWELL SERVICE

```
===== end /etc/vz/conf/1.mount =====  
=====  
VE is mounted  
Setting CPU units: 1000  
Configure meminfo: 2000000  
VE start in progress...  
TIME: 0 seconds.  
Waiting for container to finish booting.  
/usr/lib/mw/startxvnc: Becoming nobody.  
/usr/lib/mw/startxvnc: Waiting for 8-byte vncpasswd and EOF.  
1+0 records in  
1+0 records out  
8 bytes (8 B) copied, 3.5333e-05 s, 226 kB/s  
Got the vncpasswd  
Adding auth for 10.51.0.1:0 and 10.51.0.1/unix:0  
xauth: creating new authority file Xauthority-10.51.0.1:0  
Adding IP address(es): 10.51.0.1  
if-up.d/mountnfs[venet0]: waiting for interface venet0:0 before doing  
NFS mounts (warning).  
WARNING: Settings were not saved and will be resetted to original valu  
es on next start (use --save flag)
```

```
# vzlist  
      VEID      NPROC STATUS  IP_ADDR      HOSTNAME  
      1          6 running 10.51.0.1    -
```

```
# openssl s_client -connect localhost:4001
```

This should report an SSL connection with a self signed certificate and output text should end with:

```
---  
RFB 003.008
```

MAXWELL SERVICE

If you see this then you successfully connected to the VNC server running inside the newly created OpenVZ session.

Clean up

```
# maxwell_service stopvnc 1
```

Which should give output similar to:

```
Killing 6 processes in veid 1 with signal 1
Killing 7 processes in veid 1 with signal 2
Killing 5 processes in veid 1 with signal 15
Got signal 9
Stopping VE ...
VE was stopped
===== begin /etc/vz/conf/1.umount =====
=====
Unmounting /var/lib/vz/root/1/usr
Unmounting /var/lib/vz/root/1/home
Unmounting /var/lib/vz/root/1/apps
Unmounting /var/lib/vz/root/1/.root

Removing /var/lib/vz/root/1 :root etc var tmp dev/shm dev
Removing /var/lib/vz/private/1: apps bin emul home lib lib32 lib64 mnt
  opt proc sbin sys usr .root
===== end /etc/vz/conf/1.umount =====
=====
VE is unmounted
```