

# Accessing Outside Computing Resources

## Overview

Tools are hosted within a "tool session" running within the hub environment. The tool session supports the graphical interface, which helps the user set up the problem and visualize results. If the underlying calculation is fairly light weight (e.g., runs in a few minutes or less), then it can run right within the same tool session. But if the job is more demanding, it can be shipped off to another machine via the "submit" command, leaving the tool session host less taxed and more responsive.

This chapter describes the "submit" command, showing how it can be used at the command line within a workspace and also within Rappture-based tools.

# Submit Command

## Overview

submit takes a user command and executes it remotely. The objective is to allow the user to issue a command in the same manner as a locally executed command. Multiple submission mechanisms are available for run dissemination. A set of steps are executed for each run submission:

- Destination site is selected
- A wrapper script is generated for remote execution
- If needed a batch system description file is generated.
- Input files for a run are gathered and transferred to the remote site. Transferred files include the wrapper and batch description scripts.
- The wrapper script is executed remotely.
- Progress of the remote run is monitored until completion.
- Output files from the run are returned to the dissemination point.

## Command Syntax

submit command options can be determined by using the help parameter of the submit command.

```
$ submit --help
Usage: submit [options]
```

Options:

-h, --help	Report command usage. Optionally request listing of managers, tools, venues, or examples.
-l, --local	Execute command locally
--status	Report status for runs executing remotely.
-k, --kill	Kill runs executing remotely.
--venueStatus	Report venue status.
-v, --venue	Remote job destination
-i, --inputfile	Input file
-p, --parameters	Parameter sweep variables. See examples.
-d, --data	Parametric variable data - csv format
-s SEPARATOR, --separator=SEPARATOR	Parameter sweep variable list separator
-n NCPUS, --nCpus=NCPUS	Number of processors for MPI execution
-N PPN, --ppn=PPN	Number of processors/node for MPI execution

## ACCESSING OUTSIDE COMPUTING RESOURCES

---

```
--stripes=NSTRIPES      Number of parallel local jobs when doing param
etric
                        sweep
-w WALLTIME, --wallTime=WALLTIME
                        Estimated walltime hh:mm:ss or minutes
-e, --env               Variable=value
--runName=RUNNAME      Name used for directories and files created du
ring the
                        run. Restricted to alphanumeric characters
-m, --manager          Multiprocessor job manager
-r NREDUNDANT, --redundancy=NREDUNDANT
                        Number of identical simulations to execute in
parallel
-M, --metrics          Report resource usage on exit
--detach              Detach client after launching run
--attach=ATTACHID     Attach to previously detached started server
-W, --wait            Wait for reduced job load before submission
-Q, --quota           Enforce local user quota on remote execution h
ost
-q, --noquota         Do not enforce local user quota on remote exec
ution
                        host
--tailStdout          Periodically report tail of stdout file.
--tailStderr          Periodically report tail of stderr file.
--tail               Periodically report tail of application file.
--progress            Show progress method. Choices are auto, curses
,
                        submit, text, pegasus, or silent.
--asynchronous        Asynchronous simulation - results will not be
returned
```

Additional information is available by requesting user specific lists of choices for some command options. The available option lists are generated for a user based on configured restrictions and availability. The values listed here are for example only and may not be available on all HUBs.

```
$ submit --help tools
```

Currently available TOOLS are:

```
lammmps-03Mar20-parallel
lammmps-03Mar20-serial
lammmps-05Jun19-parallel
lammmps-05Jun19-serial
```

## ACCESSING OUTSIDE COMPUTING RESOURCES

---

```
lammmps-11Aug17-parallel
lammmps-11Aug17-serial
lammmps-22Aug18-parallel
lammmps-22Aug18-serial
lammmps-31Mar17-parallel
lammmps-31Mar17-serial
```

```
$ submit --help venues
```

Currently available VENUES are:

```
OSG
brown
datalimited@brown
ncn-hub@brown
standby@brown
```

```
$ submit --help managers
```

Currently available MANAGERS are:

```
lammmps-03Mar20_mpi
lammmps-03Mar20_serial
lammmps-05Jun19_mpi
lammmps-05Jun19_serial
lammmps-11Aug17_mpi
lammmps-11Aug17_serial
lammmps-22Aug18_mpi
lammmps-22Aug18_serial
lammmps-31Mar17_mpi
lammmps-31Mar17_serial
mpi
mpich
mpirun
parallel
serial
```

Examples of how to use the submit command to execute parameter sweeps are provided by asking for help on examples.

```
$ submit --help examples
Usage: submit [options]
```

Options:

```
-h, --help          Report command usage. Optionally request listi
```

## ACCESSING OUTSIDE COMPUTING RESOURCES

---

ng of

	managers, tools, venues, or examples.
-l, --local	Execute command locally
--status	Report status for runs executing remotely.
-k, --kill	Kill runs executing remotely.
--venueStatus	Report venue status.
-v, --venue	Remote job destination
-i, --inputfile	Input file
-p, --parameters	Parameter sweep variables. See examples.
-d, --data	Parametric variable data - csv format
-s SEPARATOR, --separator=SEPARATOR	Parameter sweep variable list separator
-n NCPUS, --nCpus=NCPUS	Number of processors for MPI execution
-N PPN, --ppn=PPN	Number of processors/node for MPI execution
--stripes=NSTRIPES	Number of parallel local jobs when doing parametric sweep
-w WALLTIME, --wallTime=WALLTIME	Estimated walltime hh:mm:ss or minutes
-e, --env	Variable=value
--runName=RUNNAME	Name used for directories and files created during the run. Restricted to alphanumeric characters
-m, --manager	Multiprocessor job manager
-r NREDUNDANT, --redundancy=NREDUNDANT	Number of identical simulations to execute in parallel
-M, --metrics	Report resource usage on exit
--detach	Detach client after launching run
--attach=ATTACHID	Attach to previously detached started server
-W, --wait	Wait for reduced job load before submission
-Q, --quota	Enforce local user quota on remote execution host
-q, --noquota	Do not enforce local user quota on remote execution host
--tailStdout	Periodically report tail of stdout file.
--tailStderr	Periodically report tail of stderr file.
--tail	Periodically report tail of application file.
--progress	Show progress method. Choices are auto, curses, submit, text, pegasus, or silent.
--asynchronous	Asynchronous simulation - results will not be returned

## ACCESSING OUTSIDE COMPUTING RESOURCES

---

Parameter examples:

```
submit -p @@cap=10pf,100pf,luf sim.exe @:indeck
```

Submit 3 jobs. The @:indeck means "use the file indeck as a template file." Substitute the values 10pf, 100pf, and luf in place of @@cap within the file. Send off one job for each of the values and bring back the results.

```
submit -p @@vth=0:0.2:5 -p @@cap=10pf,100pf,luf sim.exe @:indeck
```

Submit 78 jobs. The parameter @@vth goes from 0 to 5 in steps of 0.2, so there are 26 values for @@vth. For each of those values, the parameter @@cap changes from 10pf to 100pf to luf.  $26 \times 3 = 78$  jobs total. Again @:indeck is treated as a template, and the values are substituted in place of @@vth and @@cap in that file.

```
submit -p params sim.exe @:indeck
```

In this case, parameter definitions are taken from the file named params instead of the command line. The file might have the following contents:

```
# paramters for my job submission
parameter @@vth=0:0.2:5
parameter @@cap = 10pf,100pf,luf
```

```
submit -p "params;@@num=1-10;@@color=blue" job.sh @:job.data
```

For someone who loves syntax and complexity... The semicolon separates the parameters value into three parts. The first says to load parameters from a file params. The next part says add an additional parameter @@num that goes from 1 to 10. The last part says add an additional parameter @@color with a single value blue. The parameters @@num and @@color cannot override anything defined within params; they must be new parameter names.

## ACCESSING OUTSIDE COMPUTING RESOURCES

---

```
submit -d input.csv sim.exe @:indeck
```

Takes parameters from the data file `input.csv`, which must be in comma-separated value format. The first line of this file may contain a series of @@param names for each of the columns. Whitespace is significant for all values entered in the csv file. If it doesn't, then the columns are assumed to be called @@1, @@2, @@3, etc. Each of the remaining lines represents a set of parameter values for one job; if there are 100 such lines, there will be 100 jobs. For example, the file `input.csv` might look like this:

```
@@vth,@@cap
1.1,1pf
2.2,1pf
1.1,10pf
2.2,10pf
```

Parameters are substituted as before into template files such as `@:indeck`.

```
submit -d input.csv -p "@@doping=1e15-1e17 in 30 log" sim.exe @:infile
```

Takes parameters from the data file `input.csv`, but also adds another parameter `@@doping` which goes from `1e15` to `1e17` in 30 points on a log scale. For each of these points, all values in the data file will be executed. If the data file specifies 50 jobs, then this command would run  $30 \times 50 = 1500$  jobs.

```
submit -d input.csv -i @:extra/data.txt sim.exe @:indeck
```

In addition to the template `indeck` file, send along another file `extra/data.txt` with each job, and treat it as a template too.

```
submit -s / -p @@address=23 Main St.,Hometown,Indiana/42
Broadway,Hometown,Indiana -s , -p @@color=red,green,blue job.sh @:job.
```

## ACCESSING OUTSIDE COMPUTING RESOURCES

---

data

Change the separator to slash when defining the addresses, then change back to comma for the @@color parameter and any remaining arguments. We shouldn't have to change the separator often, but it might come in handy if the value strings themselves have commas.

```
submit -p @@num=1:1000 sim.exe input@@num
```

Submit jobs 1,2,3,...,1000. Parameter names such as @@num are recognized not only in template files, but also for arguments on the command line. In this case, the numbers 1,2,3,...,1000 are substituted into the file name, so the various jobs take their input from "input1", "input2", ..  
..,  
"input1000".

```
submit -p @@file=glob:indeck* sim.exe @@file
```

Look for files matching indeck\* and use the list of names as the parameter @@file. Those values could be substituted into other template files, or used on the command line as in this example. Suppose the directory contains files indeck1, indeck10, and indeck2. The glob option will order the files in a natural order: indeck1, indeck2, indeck10. This example would launch three jobs using each of those files as input for the job.

```
submit -p @@file=globnat:indeck* sim.exe @@file
```

This option has been deprecated. The functionality is now available with the glob option.

By specifying a suitable set of command line parameters it is possible to execute commands on configured remote systems. The simple premise is that a typical command line can be prefaced



## ACCESSING OUTSIDE COMPUTING RESOURCES

---

by submit and its arguments to execute the command remotely.

```
$ submit -v clusterA echo Hello world!  
Hello world!
```

In this example the echo command is executed on the venue named clusterA where runs are executed directly on the host. Execution of the same command on a cluster using a batch scheduler such as SLURM would be done in a similar fashion

```
$ submit -v clusterB echo Hello world!  
(2586337) Simulation Queued Wed Oct 7 14:45:21 2009  
(2586337) Simulation Done Wed Oct 7 14:54:36 2009  
$ cat 00577296.stdout  
Hello world!
```

submit supports an extensible variety of submission mechanisms. HUBzero supported submission mechanisms are

- local - use batch submission mechanisms available directly on the submit host. These include condorHT, and Pegasus batch queue submission.
- ssh - direct use of ssh. Submit manages access to a venue using a common ssh key, essentially serving as a proxy for the HUB user.
- ssh + remote batch submission - use ssh to do batch run submission remotely. Again methods for common batch schedulers PBS, condorHT, Pegasus, and SLURM are provided. Additional interfaces to SGE, Load Leveler, BOINC, LSF, and Tapis are also available.

In addition to single site submission the `-r/--redundancy` option provides the option to simultaneously submit runs to multiple remote venues. In such cases the successful completion of a run at one venue cancels runs at all other venues. If none of the runs are successful results from one of the runs are returned to the user. Redundant submission is not allowed when performing parametric sweeps.

A venue for remote execution is selected in one of the following ways, listed in order of precedence:

- Execute the command within the user tool session, `-l/--local` option
- User specified on the command line with `-v/--venue` option.
- Randomly selected from remote sites associated with pre-staged application.
- Select randomly from all configured sites

Venues that do not meet the resource requirements of the run request are not considered.

## ACCESSING OUTSIDE COMPUTING RESOURCES

---

Venues are typically configured with limits on the number of cores, walltime, or core-hours.

Any files specified by the user plus internally generated scripts are packed into a tarball for delivery to the remote site. Individual files or entire directory trees may be listed as command inputs using the `-i/--inputfile` option. In addition, command arguments that exist as files or directories will be packed into the tarball. If using ssh based submission mechanisms the tarball is transferred using `scp`.

The job wrapper script is executed remotely either directly or submitted to a batch queue. The job is subject to all remote queuing restrictions and idiosyncrasies.

Remote batch jobs are monitored for progress. Methods appropriate to the batch queuing system are used to check job status at a configurable frequency. A typical frequency is on the order one minute. Job status changes are reported to the user. The maximum time between reports to the user is set on the order of five minutes even in the absence of change. The job status is used to detect job completion.

The same methods used to transfer input files are applied in reverse to retrieve output files. Any files and directories created or modified by the application are be retrieved. A tarball is retrieved and expanded to the home base directory. It is up to the user to avoid the overwriting of files.

In addition to the application generated output files additional files are generated in the course of remote run execution. Some of these files are for internal bookkeeping and are consumed by `submit`, a few files however remain in the home base directory. The remaining files include `RUNID.stdout` and `RUNID.stderr`, it is also possible that a second set of standard output/error files will exist containing the output from the batch job submission script. By default, `RUNID` represents unique job identifier assigned by `submit`. If preferred a user can specify a different `RUNID` using the `--runName` command argument.

# Pegasus Workflow Submission

## Overview

Functionality has been included in submit to support workflow management using [Pegasus](#). Two use cases are available: automatic workflow generation for parametric sweeps on one or more variables, or user constructed workflows. In both instances submit is used to configure access to one or more computational resources eliminating the need for a user to supply a site catalog thereby simplifying use of the workflow management system.

## Parametric Sweeps

submit command options `-p/--parameters` and `-d/--data` provide support for specifying parameter sweeps in a compact general way. The user is relieved of the chore of generating entire sets of input files and command arguments comprising a parameter sweep. Substitutable parameters are declared on the submit command line. Values of these parameters can then be systematically substituted into data files or application command line parameters. submit performs the necessary substitutions to cover all parameter combinations. Each combination of parameters is abstractly represented as a node in a workflow and concretely executed as a job on the designated computational resource. A simple curses interface is provided to monitor progress of the simulation run.

## User Constructed Workflows

Parameter sweeps are represented as a simple workflow consisting of many individual independent nodes. That is data is not shared between nodes or jobs in the run. There are cases where this simple approach is not sufficient to describe a workflow required to achieve a developer's or user's objective. Under these circumstances a developer may create a workflow and build an application around it where the user supplies values for selected inputs. In such cases the [Pegasus API's](#) may be used to generate the abstract workflow description in the form of a dax file. The dax file can then be executed by a simple submit command.

```
submit pegasus-plan --dax daxFile
```

In cases where more than one venue is capable of executing Pegasus runs a specific venue can be requested on the command line, otherwise submit will choose a venue at random.

## ACCESSING OUTSIDE COMPUTING RESOURCES

---

```
submit -v DiaGrid pegasus-plan --dax daxFile
```

There are several additional options to pegasus-plan command that are supplied by submit. A few of the command options may be provided on the command line. submit reserves the option to silently ignore options as it sees fit.

In addition to remote execution of Pegasus runs it is also possible to do the execution locally with in the tool session. Simply use the submit -l/--local option.

```
submit --local pegasus-plan --dax daxFile
```

The use command can be employed to put pegasus-plan and all other Pegasus commands in the PATH environment variable. In addition to setting PATH, other environment variables are set allowing use of the Python and java dax generation API's.

# Rappture Integration with Submit

## Overview

It is possible to use the submit command to execute simulation jobs generated by Rappture interfaces remotely. A common approach is to create a shell script which can be exec'd or forked from an application wrapper script. This approach has been applied to TCL, Python, Octave, MATLAB, and Perl wrapper scripts. To avoid consumption of large quantities of remote resources it is imperative that the submit command be terminated when directed to do so by the application user (Abort button).

## TCL Wrapper Script

submit can be called from a TCL Rappture wrapper script for remote batch job submission. An example of what code to insert in the wrapper script is detailed here.

An initial code segment is required to catch the Abort button interrupt. Setting `execctl` to 1 will terminate the process and any child processes.

```
package require Rappture
Rappture::signal SIGHUP sHUP {
    puts "Caught SIGHUP"
    set execctl 1
}
Rappture::signal SIGTERM sTERM {
    puts "Caught SIGTERM"
    set execctl 1
}
```

A second code segment is used to build an executable script that can be executed using `Rappture::exec`. The trap statement will catch the interrupt thrown when the wrapper script execution is Aborted. Putting the submit command in the background allows for the possibility of issuing multiple submit commands from the script. The wait statement forces the shell script to wait for all submit commands to terminate before exiting.

```
set submitScript "#!/bin/sh\n\n"
append submitScript "trap cleanup HUP INT QUIT ABRT TERM\n\n"
append submitScript "cleanup()\n"
append submitScript "{\n"
append submitScript "    kill -TERM `jobs -p`\n"
```

## ACCESSING OUTSIDE COMPUTING RESOURCES

---

```
append submitScript "    exit 1\\n"
append submitScript "}\\n\\n"

append submitScript "cd [pwd]\\n"
append submitScript "submit -v cluster -n $cores -w $walltime\\\\\\\\\\n"
n"
append submitScript "        COMMAND ARGUMENTS &\\n"
append submitScript "sleep 5\\n"
append submitScript "wait\\n"

set submitScriptPath [file join [pwd] submit_script.sh]
set fid [open $submitScriptPath w]
puts $fid $submitScript
close $fid
file attributes $submitScriptPath -permissions 00755
```

The standard method for wrapper script execution of commands can now be used. This will stream the output from all submit commands contained in submit\_script.sh to the GUI display. The same output will be retained in the variable out.

```
set status [catch {Rappture::exec $submitScriptPath} out]
```

Each submit command creates files to hold COMMAND standard output and standard error. The file names are of the form JOBID.stdout and JOBID.stderr, where JOBID is an 8 digit number. These results can be gathered as follows.

```
set out2 ""
foreach errfile [glob -nocomplain *.stderr] {
    if [file size $errfile] {
        if {[catch {open $errfile r} fid] == 0} {
            set info [read $fid]
            close $fid
            append out2 $info
        }
    }
    file delete -force $errfile
}
foreach outfile [glob -nocomplain *.stdout] {
    if [file size $outfile] {
        if {[catch {open $outfile r} fid] == 0} {
            set info [read $fid]
            close $fid
            append out2 $info
        }
    }
}
```

```
    }  
    file delete -force $outfile  
}
```

The script file should be removed.

```
file delete -force $submitScriptPath
```

The output is presented as the job output log.

```
$driver put output.log $out2
```

All other result processing can proceed as normal.

### Python Wrapper Script

submit can be called from a python Rappture wrapper script for remote batch job submission. An example of what code to insert in the wrapper script is detailed here.

An initial code segment is required to import some predefined functions that manage typical aspects of remote submission. An important aspect is the handling of user interruption via the Abort button.

```
import os  
from Rappture.tools import executeCommand as RapptureExec
```

A second code segment is used to build a list containing an executable submit command to be executed using RapptureExec. RapptureExec will trap signals initiated by pressing the Abort button. The submit command must terminate before RapptureExec exits and returns control to the application wrapper script.

```
submitCommand = ["submit", "-v", venue, "-n", cores,  
                "-w", walltime, COMMAND, ARGUMENTS]  
exitStatus, stdout, stderr = RapptureExec(submitCommand)
```

The standard method for wrapper script execution of commands can now be used. This will stream the output from the submit command to the GUI display. The same output will be retained in the variable `stdOutput`.

The submit command creates files to hold COMMAND standard output and standard error. By default the file names are of the form `JOBID.stdout` and `JOBID.stderr`, where `JOBID` is an 8 digit number. These results can be gathered as follows.

```
reStdout = re.compile(".*.stdout$")
reStderr = re.compile(".*.stderr$")

out2 = ""
errFiles = filter(reStderr.search,os.listdir(os.getpwd()))
if errFiles != []:
    for errFile in errFiles:
        errFilePath = os.path.join(os.getpwd(),errFile)
        if os.path.getsize(errFilePath) > 0:
            f = open(errFilePath,'r')
            outFileLines = f.readlines()
            f.close()
            stderr = ''.join(outFileLines)
            out2 += '\n' + stderr
            os.remove(errFilePath)

outFiles = filter(reStdout.search,os.listdir(os.getpwd()))
if outFiles != []:
    for outFile in outFiles:
        outFilePath = os.path.join(os.getpwd(),outFile)
        if os.path.getsize(outFilePath) > 0:
            f = open(outFilePath,'r')
            outFileLines = f.readlines()
            f.close()
            stdout = ''.join(outFileLines)
            out2 += '\n' + stdout
            os.remove(outFilePath)
```

The output is presented as the job output log.

```
lib.put("output.log", out2, append=1)
```



All other result processing can proceed as normal.

### Perl Wrapper

submit can be called from a perl Rappture wrapper script for remote batch job submission. An example of what code to insert in the wrapper script is detailed here.

An initial code segment is required to catch the Abort button interrupt.

```
use Rappture

my $ChildPID = 0;

sub trapSig {
    print "Signal @_ trapped\\n";
    if($ChildPID != 0) {
        kill 'TERM', $ChildPID;
        exit 1;
    }
}

$SIG{TERM} = \&trapSig;
$SIG{HUP} = \&trapSig;
$SIG{INT} = \&trapSig;
```

A second code segment is used to build an executable script that can be executed using `Rappture.tools.getCommandOutput`. The trap statement will catch the interrupt thrown when the wrapper script execution is Aborted. The wait statement forces the shell script to wait for the submit command to terminate before exiting.

```
$SCRPT = "submit_app.sh";
open(FID, ">$SCRPT");
print FID "#!/bin/sh\\n";
print FID "\\n";
print FID "trap cleanup HUP INT QUIT ABRT TERM\\n\\n";
```

## ACCESSING OUTSIDE COMPUTING RESOURCES

---

```
print FID "cleanup()\n";
print FID "{\n";
print FID "    kill -s TERM `jobs -p`\n";
print FID "    exit 1\n";
print FID "}\n\n";

print FID "submit -v cluster -n $scores -w $wallTime COMMAND ARGUMENTS
&\n";
print FID "wait %1\n";
print FID "exitStatus=\\$?\n";
print FID "exit \\$exitStatus\n";
close(FID);
chmod 0775, $SCRPT;
```

The standard fork and exec method for wrapper script execution of commands can now be used. Using this approach does not allow streaming of the command outputs.

```
if      (!defined($ChildPID = fork())) {
    die "cannot fork: $!";
} elsif ($ChildPID == 0) {
    exec("./$SCRPT") or die "cannot exec $SCRPT: $!";
    exit(0);
} else {
    waitpid($ChildPID,0);
}
```

Each submit command creates files to hold COMMAND standard output and standard error. The file names are of the form JOBID.stdout and JOBID.stderr, where JOBID is an 8 digit number. These results can be gathered with standard perl commands for file matching, reading, etc. All other result processing can proceed as normal.

### Octave/MATLAB Script

submit can be called from a Octave or MATLAB Rappture wrapper script for remote batch job submission. An example of what code to insert in the wrapper script is detailed here.

```
-- Function: [EXITSTATUS] = rpExec(COMMAND,STREAMOUTPUT)
-- Function: [EXITSTATUS, STDOUTOUTPUT] = rpExec(COMMAND,STREAMOUTPUT)
-- Function: [EXITSTATUS, STDOUTOUTPUT, STDERROR] = rpExec(COMMAND,STREA
```

## ACCESSING OUTSIDE COMPUTING RESOURCES

---

MOUTPUT)

Execute COMMAND with the ability to terminate the process upon reception of a interrupt, hangup, or terminate signal. Doing so allows the process to be terminated when the Rappture "Abort" button is pressed. COMMAND should contain a set of strings that compris

e

the command to be executed. If STREAMOUTPUT equals 1 the stdout and stderr from COMMAND are piped back to the current process stdout and stderr descriptors as COMMAND executes.

On output EXITSTATUS indicates whether or not an error occurred. EXITSTATUS equals 0 indicates that no error occurred. If STDOUTPU

T

is supplied it will contain a copy of stdout from COMMAND. In th

e

same manner if STDERROR is supplied it will contain a copy of stderr from COMMAND.

Example:

```
[exitStatus,stdout,stderr] = rpExec({"submit","-wallTime","30","lammps-12Feb14-serial","-in","lmp.in"},1);
```